

**Technical parameters for solid fuel local space heaters**  
**EU 2015/1186 of 24 April 2015**

Model identifier(s): **JØTUL FS 173**

Indirect heating functionality: no

Direct heat output (kW): 7,5 kW


Indirect heat output (kW): N.A

Fuel	Preferred fuel (only one):	Other suitable fuel(s):
Wood logs with moisture content $\leq 25\%$	Yes	No
Compressed wood with moisture content $< 12\%$	No	No
Other woody biomass	No	No
Non-woody biomass	No	No
Anthracite and dry steam coal	No	No
Hard coke	No	No
Low temperature coke	No	No
Bituminous coal	No	No
Lignite briquettes	No	No
Peat briquettes	No	No
Blended fossil fuel briquettes	No	No
Other fossil fuel	No	No
Blended biomass and fossil fuel briquettes	No	No
Other blend of biomass and solid fuel	No	No

**Characteristics when operating with the preferred fuel**

Seasonal space heating energy efficiency  $\eta_s$  [%]: 67

Energy Efficiency Index (EEI): 102

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Heat output</b>				<b>Useful efficiency (NCV as received)</b>			
Nominal heat output	$P_{nom}$	7,5	kW	Useful efficiency at nominal heat output	$\eta_{th,nom}$	77	%
Minimum heat output (indicative)	$P_{min}$	N.A.	kW	Useful efficiency at minimum heat output (indicative)	$\eta_{th,min}$	N.A.	%
<b>Auxiliary electricity consumption</b>				<b>Type of heat output/room temperature control (select one)</b>			
At nominal heat output	$e_{l_{max}}$	x,xxx	kW	single stage heat output, no room temperature control	[yes/no]		
At minimum heat output	$e_{l_{min}}$	x,xxx	kW	two or more manual stages, no room temperature control	[yes/no]	Yes	
In standby mode	$e_{l_{sb}}$	x,xxx	kW	with mechanic thermostat room temperature control	[yes/no]		
				with electronic room temperature control	[yes/no]		
				with electronic room temperature control plus day timer	[yes/no]		
				with electronic room temperature control plus week timer	[yes/no]		
				<b>Other control options (multiple selections possible)</b>			
				room temperature control, with presence detection	[yes/no]		
				room temperature control, with open window detection	[yes/no]		
				with distance control option	[yes/no]		
<b>Permanent pilot flame power requirement</b>				Signature:			
Pilot flame power requirement (if applicable)	$P_{pilot}$	N.A.	kW	 Espen Auensen, R&D Manager			
Contact details	Name and address of the supplier: Jøtul AS, P.O. box 1411, 1602 Fredrikstad, Norway						